

SUITABLE MOST OF TESTERS

DOUBLE INSULATION WITH
DAMAGE INDICATION

MP-KAMP12



MP-ACC016E



MP-ACC063



All components precision engineered and stringently tested-repetitive pull-out force tests, bending, twisting and rigidity stress tests and extreme temperature tests-to provide a long life of accuracy and consistency

 **Designed in UK**

Test Leads for accuracy, consistency and a long life

Advance Features

- For use with most leading brands of test instruments
- Double insulated cable with dual colour for damage indication
- International colour coding
- Contact resistant safety features for example, finger guards
- Combination sets for all purpose

MP-ACC016E, 3 wire fused distribution board leads & IEC connector

- 1 x 3 wire distribution board test lead
- IEC mains connector
- 2 fused crocodile clips
- Piggy back facility for 2 wire testing
- Standard compliance : BS EN 61010-031 CAT III 600V

MP-ACC063, 3 wire non-fused distribution board test lead set for MP-MFT20

- 1 x 3 wire distribution board test lead
- Universal 4 mm connector for instrument
- 3 x probes
- 3 x crocodile clips
- Earth probe has piggy back feature for two wire testing
- Standard compliance : BS EN 61010-031 CAT III 600V

MP-KAMP12, Mains lead with 3 x 4mm connectors

- Mains HOT lead with 3 x 4mm connectors

- Features and specifications are subject to change without prior notice.