

## Non-contact Voltage Tester Series

**TIPS GLOW RED** WHEN VOLTAGE DETECTED

**EASY 2 x AAA BATTERY CHANGE** 

HAS ADJUSTABLE **DUAL SENSITIVITY** 

**ONLY FOR MP-VT20** 



## Non-contact Voltage Tester



Advance Features			
MP-VT10	MP-VT20	MP-VT30	
*	*	*	
*	*	*	
*	*	*	
*	*	*	
	*		
	*		
	*		
	*		
	*		
	*		
		*	
	MP-VT10 *  *  *	MP-VT10 MP-VT20  *	

- Features and specifications are subject to change without prior notice.



MEET INTERNATIONAL LTD. 🚾

Flat C, 11/F., China Trade Centre, 122-124 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2950 4689 E-mail: sales@meet.com.hk Website: www.meet.com.hk

www.globalsources.com/meetintl.co

http://meetusa.en.alibaba.com Copyright © 2018 Meet International Ltd. All rights reserved







# Non-contact Voltage Tester Series

#### **SPECIFICATIONS for MP-VT10 & MP-VT20**

Standard	BSEN61010 CAT IV 600V,	
	回 Double insulated	
Operating Range	90-600 VAC	
Operating Temperature :	-10°C to 50°C	
Humidity	Max 90%	
Battery Powered	2 x AAA (LR03/LR03)	

## **SPECIFICATIONS for MP-VT30**

Operating Voltage Range	90-600V AC 50Hz / 60Hz	
Operating Temperature	-10°C - 50°C	
Humidity	Max 90%	
Safety Compliance	EN61010-1:2010	
EMC	EN61326	
Overvoltage Category	CAT IV 600V	
Safety Compliance	BS EN 61010-2-030 : 2010	
Battery Powered	2 x AAA (LR03 / LR03)	

- Features and specifications are subject to change without prior notice.



MEET INTERNATIONAL LTD. MA

Flat C, 11/F., China Trade Centre, 122-124 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong.

Tel: (852) 2950 4689 E-mail: sales@meet.com.hk Website: www.meet.com.hk

www.globalsources.com/meetintl.co

http://meetusa.en.alibaba.com Copyright © 2018 Meet International Ltd. All rights reserved

