

# Mini Sound Level Meter with Temperature



**Model No.:MS-911**



## Advance Features:

- Measuring range 35 to 135dB
- dBA frequency weighting
- Fast / Slow response select
- Convert temperature in °C /°F
- Color LCD display with backlight
- Over range indication, low battery indication
- MAX. / MIN. record reading
- Enable / Disable Auto Power Off (APO)

<b>Specifications</b>	
<b>Model</b>	<b>MS-911</b>
Measuring Range	35dB ~ 135dB
Accuracy	± 2.0dB
Frequency Range	31.5Hz ~ 8KHz
Frequency Weighting	dBA
Dynamic Range	50dB
Time weighting	Fast:125ms / Slow:1s
Temperature Range	-20°C ~ 70°C / -4°F ~ 158°F
Temperature Accuracy	± 1.5°C/2.7°F
Temperature Resolution	0.1
Microphone	1/2 inch electret condenser microphone
High/Low reading indication	LCD displays Hi (> 100db), LCD displays LO (< 100db)
Microphone	1/2 inch electret condenser microphone
Operating Conditions	-20~60°C/-4°F ~ 140°F ;10%RH~90%RH
Storage Conditions	-20~60°C/-4°F ~ 140°F ;10%RH~75%RH
Battery Powered	3 x AAA (R03 / LR03)
Battery Life	> 60 hours (Alkaline type)
Dimension (LxWxH) mm	144 x 56 x 31
Weight (approx.) grams	75

- Features and specifications are subject to change without prior notice.



**美特國際有限公司 MEET INTERNATIONAL LTD.** MANUFACTURER AND EXPORTER

香港九龍觀塘鴻圖道26號威登中心19樓1901室

Flat 1901, 19/F, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Tel : (852) 2950 4689

E-mail : sales@meet.com.hk

Website : www.meet.com.hk

www.globalsources.com/meetintl.co

http://meetusa.en.alibaba.com

Copyright © 2017 Meet International Ltd. All rights reserved



www.meet.com.hk