

# Mini light Meter with Temperature

Model No.:MS-912



## Advance Features:

- 0 to 200,000 Lux
- Auto rang
- Measures Lux or Foot-Candles (Fc)
- High accuracy and rapid response sampling time
- Convert temp. in °C / °F
- Color LCD display with backlight
- Over range indication
- MAX / MIN record reading
- Enable / Disable power
- Low battery indication
- Hold / Freeze reading

## Specifications

Model	MS-912
Range(Lux/Fc)	0 ~200k Lux/0 ~20K Fc
Accuracy	(<10.000Lux) ±3% rdg ±8d ; (>10.000Lux) ±4% rdg ±10d
Range (Temp.)	-20~70°C/4°F ~158°F
Accuracy (Temp.)	±1.5°C /2.7°F
Spectral Accuracy	CIE Vλ function (f1' ≅ 6%f2' ≅ 2%)
Sampling Rate	2 / Sec.
Resolution (Lux)	0.1 (<1000);1.0 (>1000)
Resolution (Temp.)	0.1
Operating Condition	-20~60°C/-4 ~140°F;10%RH~90%RH
Storage Condition	-30~60°C/-4 ~140°F;10%RH~75%RH
Battery Powered	3 x AAA (R03 / LR03)
Battery Life	> 60 hours (Alkaline type)
Dimension (LxWxH) mm	174.5x56x31
Weight (approx.) grams	85

- Features and specifications are subject to change without prior notice.



美特國際有限公司 MEET INTERNATIONAL LTD. MANUFACTURER AND EXPORTER

香港九龍觀塘鴻圖道26號威登中心19樓1901室

Flat 1901, 19/F., Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Tel : (852) 2950 4689 E-mail : sales@meet.com.hk

Website : www.meet.com.hk

www.globalsources.com/meetintl.co

http://meetusa.en.alibaba.com

Copyright © 2017 Meet International Ltd. All rights reserved



www.meet.com.hk

