

Light Meter

Model No.:MS-932

Advance Features:

- Analog bar-graph indication
- MAX / MIN record reading
- Lux / Fc selection
- Auto Power-off
- Hold / Freeze reading
- Auto or Manual range select
- Blacklight



Specifications	
Model	MS-932
Range(Lux/Fc)	0~400k Lux, 0~40k Fc
Accuracy	(<10,000Lux) $\pm 3\%$ rdg $\pm 0.5\%$ f.s. ; (>10,000Lux) $\pm 4\%$ rdg ± 10 dgts
Sampling Rate	2 / Sec.
Spectral Response	CIE photopic (CIE human eye response curve)
Over /Under Range Indication	Over range LCD displays '-OL-' (over) or '-LO-' (under)
Spectral Accuracy	CIE V_{λ} function ($f_1' \cong 6\%$, $f_2' \cong 2\%$)
Sensor Lead Length	>1.5m
Sensor	Silicon photo-diode with spectral response filter
Operating and Storage Condition	0~50°C / 32 ~ 122°F; < 90%RH
Battery Powered	1 x 9V (6F22 / 6LR61 / 1604)
Dimension (LxWxH) mm	159x62x33
Weight (approx.) grams	230 (Without battery)

- Features and specifications are subject to change without prior notice.



美特國際有限公司 MEET INTERNATIONAL LTD.

香港九龍觀塘鴻圖道26號威登中心19樓1901室

Flat 1901, 19/F., Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Tel : (852) 2950 4689

E-mail : sales@meet.com.hk

Website : www.meet.com.hk

www.globalsources.com/meetintl.co

www.meetishop.com

Copyright © 2022 Meet International Ltd. All rights reserved



meet.com.hk

