

Thermo Hygrometer Meter

Model No.:MS-933

Advance Features:

- °C / °F select
- MAX. / MIN. reading display
- Hold / Freeze reading
- Dew Point temp. reading
- Auto Power Off
- Self-calibration function



Specifications			
Model	MS-933		
	Measuring Range	Accuracy	Resolution
Humidity	0 ~ 100%RH	40~60%RH: ± 2.0%RH	0.1
		20~40%RH: ± 3.0%RH	
		60~80%RH: ± 3.0%RH	
		0~20%RH: ± 4.0%RH	
		80~100%RH: ± 4.0%RH	
Temperature	-20°C ~ 70°C -4°F ~ 158°F	-20~70°C / -4°F ~ 158°F ± 1.0°C / 1.8°F	
Dew Point Temp.	-20°C ~ 70°C -4°F ~ 158°F	-20~70°C / -4°F ~ 158°F ± 1.0°C / 1.8°F	
Response time	1second		
Sampling rate	1 / Sec.		
Operating Condition	-20°C ~ 60°C / -4°F ~ 140°F : < 90%RH (Non-condensation)		
Storage Condition	-20°C ~ 70°C / -22°F ~ 158°F : < 70%RH		
Battery Powered	1 x 9V (6F22 / 6LR61 / 1604)		
Dimension (LxWxH) mm	192 x 62 x 33mm		
Weight (approx.) grams	150		

- Features and specifications are subject to change without prior notice.



美特國際有限公司 MEET INTERNATIONAL LTD. MANUFACTURER AND EXPORTER

香港九龍觀塘鴻圖道26號威登中心19樓1901室

Flat 1901, 19/F, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Tel : (852) 2950 4689 E-mail : sales@meet.com.hk

Website : www.meet.com.hk

www.globalsources.com/meetintl.co

http://meetusa.en.alibaba.com



www.meet.com.hk