

Anemometer

Model No.:MS-935



Advance Features:

- Flexible remote sensor
- Air velocity level indication (bar type display)
- Blacklight
- Convert area setting : CM² / m² / ft²
- Convert air velocity : m/s; Km/h; ft/min; Knots; Mph
- Convert temp. : °C / °F



Specifications	
Model	MS-935
Air Velocity Range	0.3 ~ 45.0m/s 1.0 ~ 162.0km/s 59 ~ 885ft/min
	0.5 ~ 87.5knots 0.6 ~ 100.6Mph
	-30°C ~ 60°C / -22°F ~ 140°F
Air Temp. Accuracy	±1.5°C / 2.7°F
Air Velocity. Accuracy	±3% ±0.1
Resolution	0.1
Sampling Rate	1 / Sec.
Operating Temperature	-20°C ~ 60°C / -4°F ~ 140°F
Operating Humidity	<90%RH (Non-condensation)
Storage Temperature	-30°C ~ 70°C / -22°F ~ 158°F
Storage Humidity	<75%RH
Air Velocity Level Indication	level 0-16 with analog bar-graph
Average Measurement	average reading of the latest 10 records
Convert area	0.001~9999m ² (0.001~9999ft ²)
Battery Powered	1 x 9V (6F22 / 6LR61 / 1604)
Dimension(LxWxH)	160 x 62 x 33
Weight (approx.) grams	280

- Features and specifications are subject to change without prior notice.



美特國際有限公司 MEET INTERNATIONAL LTD. MANUFACTURER AND EXPORTER
香港九龍觀塘鴻圖道26號威登中心19樓1901室
Flat 1901, 19/F, Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong
Tel : (852) 2950 4689 E-mail : sales@meet.com.hk
Website : www.meet.com.hk www.globalsources.com/meetintl.co



www.meet.com.hk

http://meetusa.en.alibaba.com

Copyright © 2017 Meet International Ltd. All rights reserved