

**Wireless Data
logger compatible**

Wireless Connectivity Formaldehyde + Thermo-Hygrometer

Monitoring anytime and even > 10 meters away (point to point)



Digital display

MS-WFD
Formaldehyde Meter +
Thermo-Hygrometer



Capture picture
with data
on screen display



Analogue display
(Turn clockwise)

Specifications		
Model No.:	Require External Wireless Module	MS-WFD
Operating voltage		4.5 V
Operating current		< 150mA
Standby current		< 10uA
Formaldehyde measuring range		HCHO : 0.000 ~ 3.000 PPM (0.000 ~ 4.020mg / m3) TVOC : 0.000 ~ 3.000 PPM (0.000 ~ 10.461mg / m3) Over range display 'Hi'
Ambient temperature measuring range and accuracy		-40.0°C (-40.0°F) ~ 0.0°C (32.0°F) / 0.0°C (32.0°F) ~ 70.0°C (158.0°F) (± 0.5°C (0.9°F)) 70.0°C (158.0°F) ~ 100.0°C (212.0°F) (± 1.0°C (1.8°F))
Ambient humidity measuring range and accuracy		0% ~ 20% RH / 80% ~ 100%RH (± 5% RH @ 25.0°C (77.0°F)) 20% ~ 80% RH (± 4% RH @ 25.0°C (77.0°F))
Resolution		0.001 PPM / mg/m3; (temperature) 0.1 °C / °F; (Humidity) 1 % RH
Max. display		*
Backlight ON/ OFF selectable		*
Low battery indication		< 2.8 V
Storage temperature and humidity		0°C (32°F) ~ 60°C (140°F) / < 80% RH
Standalone mode (without external wireless module)		*
Wireless connectivity transmit data to Smart phone / Tablet with iOS APPS or Android APPS (require MS-WMB1 external wireless module, sold separately)		*
Battery powered		3 x AAA (R03 / LR03)
Dimensions (LxWxD) mm		105 x 54 x 43
Weight (approx.) grams (without battery)		82



美特國際有限公司 MEET INTERNATIONAL LTD.

香港九龍觀塘鴻圖道26號威登中心19樓1901室

Flat 1901, 19/F., Westin Centre, 26 Hung To Road, Kwun Tong, Kowloon, Hong Kong

Tel : (852) 2950 4689

E-mail : sales@meet.com.hk

Website : www.meet.com.hk

www.globalsources.com/meetintl.co

www.meetishop.com

meet.com.hk



Copyright © 2022 Meet International Ltd. All rights reserved

CAT23008_WFD_V00