Wireless Connectivity IR Thermometer



Introduction:

MS-BIT01 / MS-BIT02 and MS-WIT02 series Wireless Connectivity Infrared Thermometer is compact in size and easy to use. It can determine the surface temperature by measuring the amount of infrared energy radiated by the target's surface or by contact using a thermocouple probe as well as ambient temperature. IR Thermometer is specially designed for use in heating ventilating, air conditioning (HVAC), plumbing, electrical, electronic, machinery and food / catering applications.

> Wireless module for multi devices

Digital display

One of the most advantages of the meter is wirelessly connect to Smart phone / Tablet / PC (require different modules, sold separately) to view data, record reading, capture picture with data on it and send the information to headquarter as well as data logging.

Specifications:

Bluetooth Integrated	'B' Series	☐ MS-BIT01	☐ MS-BIT01K	☐ MS-BIT02	☐ MS-BIT02K
Require External Wireless Modu	le 'W' Series			☐ MS-WIT02	☐ MS-WIT02K
'K' type thermocouple temperature			*		*
Ambient (Air) temperature from -20°C ~ 70°C (-4°F ~ 158°F)		*	*	*	*
Object (Surface) from -50 °C ~ 600 °C (-58°F ~ 1112 °F)		*	*	*	*
Thermocouple measureable from -50 °C ~ 1000 °C (-58°F ~ 1832°F)			*		*
Resolution 0.1 °C (0.1°F)		*	*	*	*
Max. / Min. / Diff. / Avg. reading				*	*
Hi / Lo alarm				*	*
Emissitivity		1 ~ 100	1 ~ 100	0.05 ~ 1.00	0.05 ~ 1.00
Distance to spot (D:S): 12:1		*	*	*	*
Laser pointer		*	*	*	*
Back light		*	*	*	*
Audible sound		*	*	*	*
Hold / Freeze reading		*	*	*	*
'K' type temperature Ni-Cr and Ni-Si sensor, temperature range measureable -40°C ~ 250°C (-40°F ~ 482°F) (included)			*		*
Standalone mode (without wireless module)				MS-WIT02	MS-WIT02K
Wireless connectivity transmit data to Smart phone / Tablet with iOS APPS or Android APPS (require wireless module MS-WMB1, sold separately)				MS-WIT02	MS-WIT02K
Data logger compatible (require wireless with memory module MS-WMBM1, sold separately)				MS-WIT02	MS-WIT02K
Standalone mode or Bluetooth Connectivity transmit data to Smart phone / Tablet with iOS APPS or Android APPS		MS-BIT01	MS-BIT01K	MS-BIT02	MS-BIT02K
Battery powered (included)		1 x 9V (6F22 / 6LR61 / 1604)			
Dimensions (LxWxD) mm	'B' Series	153x120x42			
	'W' Series	170x120x42			
Weight (approx.) grams	'B' Series	146 (without battery)			
	'W' Series	160 (without battery)			
1 .7 561165		Too (Milliout Bullot))			



Data logger compatible (For 'W' series)



Analogue display



Real time digital and graphic display



Capture picture with data on screen display



Historical storage / documents memory




send / share



Tel: (852) 2950 4689

Website: www.meet.com.hk





MEET INTERNATIONAL LTD. MA Flat C, 11/F., China Trade Centre, 122-124 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong.

E-mail: sales@meet.com.hk

www.globalsources.com/meetintl.co



'W' Series

'B' Series

Bluetooth Integrated